DiMES and PFC relevant experiments from DIII-D

- General Tokamak Issues and DiMES activities
- Planning for 2005

```
C. Wong (GA), D. Rudakov (UCSD)
R. Bastasz, W. Wampler, J. Whaley (SNL)
J. Brooks (ANL), P. West, T. Evans, R. Deranian (GA)
```

```
R. Doerner (UCSD), J. Watkins (SNL), N. H. Brooks (GA)
S. Allen, C. Lasnier (LLNL), D. Whyte (UW)
P. Stangeby, A. McLean (U of Toronto)
W. Jacob (IPP, Germany)
```



US PFC Technology Meeting, Dec. 6-8, 2004, Livermore, CA.

General PFC and ITER PFC issues and R&D items related to DiMES in DIII-D

(Active items in 04)

- 1. Surface material transport including C and tritium
 - C-13 experiments in DIII-D
 - Temperature control DiMES gap experiments
 - Dust collection and characterization by INEEL
 - QMB in DIII-D
- 2. Deposited tritium removal
 - Heated chamber oxidation experiment in DIII-D supported by DiMES
 - Heated DiMES: measurement of deuterium up-take
- 3. Disruptions
 - Disruption mitigation, corresponding erosion difference measured by DiMES with and without mitigation.

4. Type-I ELMs

- ELM suppression with stochastic magnetic boundary, surface erosion measurement using DiMES
- QH mode ELM free operation
- DiMES measurement of erosion from DIII-D disruption to simulate ITER ELM effects
- 5. Divertor heat flux, material erosion and re-deposition
 - Detached plasma using D, Ne or Ar gas...DiMES experiments to measure net erosion
 - DiMES solid surface material exposure, e.g. L-mode discharges
- 6. Uncertainty in edge behavior, including chamber wall erosion for long pulse and steady state devices
 - Proposed systematic study of surface material evolution using the multiple materials DiMES sample
 - Continuing coordination with the larger atomic physics community and benchmarking with DiMES experiments
 - Chamber wall erosion simulation by using upper single-null exposure and by using multiple materials DiMES sample
 - Fast probe measurements
 - DiMES porous plug experiment
 - Proposed outboard DiMES and fast probe mechanism

7. Divertor and chamber wall materials selection

- DiMES W-rod experiment (sample returned to SNL)
- DiMES multiple materials exposure including Be
- Li-DiMES experiment

8. Diagnostics development

- Hydrogen sensor
- Advanced langmuir probe development in DiMES
- Magnetic field sensor testing in DiMES
- Metallic mirror testing in DiMES
- Proposed smart tiles development in DIII-D
- Bench mark of IR camera measurement


10 Predictive modeling

- Modeling benchmark by DiMES experiments
- 11. SOL physics uncertainties
 - Benchmarked by DiMES experiments and modeling

Li-DiMES and additional hard wares

Tile currents

Successful



current monitors



DiMES rack with power supply




DiMES internal cables terminal


Recent Results from DiMES 98

Exposed to 6 L-mode discharges with sweeping OSP



The net erosion was less than +- 10 nm, i.e.. less than the uncertainty of the measurement (+- 10 nm).






Physics parameters will be analyzed for modeling input

DiMES and DIII-D ALPS 2005 Activities

- Dedicated experiments proposed: (up to end of March 2005)
 - Complete the support of the porous plug experiment
 - Metallic mirror experiment -
 - Multiple materials erosion "simulate chamber"
 - Detached plasma using Ar gas
- Piggyback and supporting other experiments:
 - Hydrogen sensor
 - Dust collection by P. Sharp of INEEL
 - C dust migration
 - Tile current measurement prepared for Li-DiMES
 - Melted layer under disruption, simulated by Al coating
 - QMB sensor
 - Magnetic field sensor
 - Disruption and ELM experiments
- Atomic data and modeling
 - Modeling could focus on SOL and the gap experiments
- Hardware modifications:
 - Raise DiMES to new lower divertor floor level plus DiMES system improvements
 - Mid-plane DiMES and fast probe (proposed)
- Others
 - IR camera benchmark
 - Advanced diagnostics



Mirror DiMES

